

Feature / Spec

- 60W/120W/240W RMS Max Power
- AC 115V, 60Hz
- 3 XLR Microphone inputs with selectable phantom power (Mic 1 has selectable priority)
- Telephone paging input
- Music on hold output
- 5 zoned speaker outputs (70 or 25V)
- Non-zoned 4/8/16 Ohm output
- RCA or XLR line output
- Front Bass and Treble controls
- Individual volume control for each input
- Master digital volume control
- Digital front panel lock
- RS232 input for integration with popular control systems
- Dimensions (WxDxH): 16.7" x 12" x 3.5" (425 x 305 x 88 mm)

- IMP-60WU Public Address Mixing Amplifier w/UM Module
- IMP-60WT Public Address Mixing Amplifier w/TM Module

- IMP-120W Public Address Mixing Amplifier
- IMP-120WU Public Address Mixing Amplifier w/UM Module
- IMP-120WT Public Address Mixing Amplifier w/TM Module

- IMP-240W Public Address Mixing Amplifier
- IMP-240WU Public Address Mixing Amplifier w/UM Module
- IMP-240WT Public Address Mixing Amplifier w/TM Module

UM Module : Anti-Shock CD/USB/SD/Tuner module



TM Module : AM / FM Tuner module

