



# Pro Mix-60

## Pro-Mix 60 Features:

- \* 3 Microphone XLR jack inputs with Line selector and Phantom Power On/Off switch
- \* 3 Aux RCA jack inputs with Individual gain control
- \* Line & Tape RCA Jack output
- \* 8 Way Screw Type Connector, for (PTT, DC +24V, 8 Ohm, 70V, 100V)
- \* 2 Tone Chimes Keys (ALE, Chimes)
- \* Treble & Bass tone controls
- \* Telephone / Emergency 3 pin Euro Type Connector
- \* Short circuit and thermal shutdown circuit protection
- \* Rear Panel Fan Speed Cooling
- \* Chimes is first priority and second is Mic 1
- \* Push to talk (PTT) muting on microphone 1
- \* Dimensions: 400 W x 60 H x 200 D without Ear
- \* Frequency Response: 50Hz~15KHz
- \* 2U Option Rack space ear



## Specifications

Output power	60W RMS, 8 Ohm < 1% THD+N 60W RMS, 70V < 1% THD+N 60W RMS, 100V < 1% THD+N
Mic input	2.8mV/10kΩ
Aux input	40mV/47kΩ
Speaker output	4/8/16Ω, 70/100V
Frequency range	55-15,000Hz(+0dB,-3.0dB)
Tone control :	
Bass	+/-10dB
Treble	+/-10dB
S/N ratio :	
Mic	better than 55 dB
Line	better than 60 dB
Aux	better than 70 dB
TEL	better than 70 dB
THD	< 2%

Admiss. ambient temp.	0-50 °C
Inputs :	
2 x mic	6.3mm jack
1 x aux	6.3mm jack
Inputs Sensitivity :	
Mic	-50dB
Line	-20dB
Aux	-12dB
TEL	-10dB
Power supply	Switchable AC115V/230V, DC 24V
AC Input	3-pin IEC jack
12V DC current	Screw terminals
Dimension	19" W x 13.3" D x 3.6" H